



CHG: ADDN KEFFA, NIFOT, DEL EPAXU

RNAV STAR RWY 12

IDNIS 3A KEFFA 1A NIFOT 1A OSDIL 3A ROGTU 3A XORMU 3A

AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

- DME/DME OPS:** NOT SUPPORTED
- ROUTES:** RNAV PROC CODING ON THE VERSO OF THE CHART
ATC WILL GIVE DESCENT CLEARANCES
- WPT CONSTRAINTS:** ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC
- CD OPS:** BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR
- NOISE ABATEMENT:** AVOID OVERFLYING THE CITY OF PORI BELOW 2000
- RCF:** SELECT TRANSPONDER CODE 7600
- RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED: FOLLOW THE STAR TO THE RESPECTIVE RWY AND EXECUTE IAP AND LAND
- DURING RADAR VECTORED BEFORE IAF: IN ACCORDANCE WITH THE RULES OF THE AIR

EFPO RNAV STAR RWY 12										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Constraints		
			ID	Flyover				LVL	LVL	Speed
IDNIS 3A RNAV 1	010	IF	IDNIS	-	-	-	-	F100+		
	020	TF	RUBOP	-	321°	329.9°T	20.7			
	030	TF	MABOM	-	297°	305.7°T	11.2	A2200+		K240-
	040	TF	REPLU	-	027°	035.4°T	5.0	A2200+		

KEFFA 1A RNAV 1	010	IF	KEFFA	-	-	-	-	F100+		
	020	TF	MABOM	-	018°	026.8°T	13.2	A2200+		K240-
	030	TF	REPLU	-	027°	035.4°T	5.0	A2200+		

NIFOT 1A RNAV 1	010	IF	NIFOT	-	-	-	-	F100+		
	020	TF	RUBOP	-	359°	007.1°T	14.8			
	030	TF	MABOM	-	297°	305.7°T	11.2	A2200+		K240-
	040	TF	REPLU	-	027°	035.4°T	5.0	A2200+		

OSDIL 3A RNAV 1	010	IF	OSDIL	-	-	-	-	F100+		
	020	TF	VANOT	-	236°	244.4°T	11.4	A2200+		K240-
	030	TF	REPLU	-	207°	215.6°T	5.0	A2200+		

ROGTU 3A RNAV 1	010	IF	ROGTU	-	-	-	-	F100+		
	020	TF	REPLU	-	065°	073.8°T	15.8	A2200+		

XORMU 3A RNAV 1	010	IF	XORMU	-	-	-	-	F100+		
	020	TF	VESAP	-	291°	299.9°T	24.2			
	030	TF	VANOT	-	297°	305.9°T	11.2	A2200+		K240-
	040	TF	REPLU	-	207°	215.6°T	5.0	A2200+		

RNAV Holdings							
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM
REPLU	125.5°T	117°	Right	K230-	A2200	1 MIN	-

WPT COORD
SEE PAGE EFPO AD 2.15 - 1