



RNAV SID RWY 18

BEDSO 1M BEXUL 1M NEPIX 1M

- DME/DME OPS: NOT SUPPORTED
- ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART
- SQUAWK: WHEN LINING UP SQUAWK THE ASSIGNED CODE
- INITIAL CLIMB: MNM TURNING ALTITUDE ACCORDING TO RTE CODING.
CLOSE-IN OBSTACLES EXIST, SEE EFKE AD 2.10 - 5
- NOISE ABATEMENT: AFTER TAKE-OFF CLIMB AS RAPIDLY AS PRACTICABLE TO AT LEAST 2000 FT ABOVE AD ELEV
PUBLISHED SID ROUTES ARE ALSO MINIMUM NOISE ROUTINGS
- AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

CHG: new PROC

EFKE RNAV SID RWY 18										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
BEDSO 1M RNAV 1	010	CA	-	-	177°	188.0°T	-		A540+	
	020	DF	AWSIZ	-	-	-	-			K180-
	030	TF	DIRGU	-	176°	187.5°T	5.5	L		
	040	TF	BEDSO	-	132°	143.1°T	17.4			
BEXUL 1M RNAV 1	010	CA	-	-	177°	188.0°T	-		A540+	
	020	DF	AWSIZ	-	-	-	-			K180-
	030	TF	BEXUL	-	227°	238.1°T	11.8			
NEPIX 1M RNAV 1	010	CA	-	-	177°	188.0°T	-		A540+	
	020	DF	AWSIZ	-	-	-	-			K180-
	030	TF	EGJUL	-	267°	277.5°T	5.0	R		K210-
	040	TF	FEBJU	-	356°	007.3°T	5.2			
	050	TF	XULBI	-	356°	007.3°T	10.7	R		
	060	TF	NEPIX	-	052°	063.1°T	18.8			

WPT COORD

SEE PAGE EFKE AD 2.15 - 1