


BRG are MAG
TR in brackets are TRUE
DIST in NM
ELEV and ALT in FT



RNAV STAR RWY 03

DODAM 2B EBEBU 1B RIKUM 2B SOTUP 1B

NAV SPECIFICATION: RNAV 1 OR P-RNAV APPROVAL REQUIRED. OTHERWISE ADVISE ATC

AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3

DME/DME OPS: NOT SUPPORTED

ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART
ATC WILL GIVE DESCENT CLEARANCES

WPT CONSTRAINTS: ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE FOLLOWED AS
PUBLISHED UNLESS EXPLICITLY CANCELLED BY ATC

CD OPS: BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING TO STAR

RCF: SELECT TRANSPONDER CODE 7600

RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED: FOLLOW THE
STAR TO THE RESPECTIVE RWY AND EXECUTE IAP AND LAND

CHG: RADIO DATA

EFMA RNAV STAR RWY 03										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
DODAM 2B RNAV 1 or P-RNAV	010	IF	DODAM	-	-	-	-		F100+	
	020	TF	RATSO	-	096°	102.1°T	9.8		A1900+	K240-
	030	TF	NARIL	-	107°	113.1°T	5.0		A1900+	

EBEBU 1B RNAV 1 or P-RNAV	010	IF	EBEBU	-	-	-	-		F100+	
	020	TF	VASET	-	234°	240.6°T	18.3	R	A1900+	K240-
	030	TF	NARIL	-	287°	293.4°T	5.0		A1900+	

RIKUM 2B RNAV 1 or P-RNAV	010	IF	RIKUM	-	-	-	-		F100+	
	020	TF	NARIL	-	082°	087.9°T	11.0		A1900+	
	-									

SOTUP 1B RNAV 1 or P-RNAV	010	IF	SOTUP	-	-	-	-		F100+	
	020	TF	VASET	-	219°	225.6°T	29.5	R	A1900+	K240-
	030	TF	NARIL	-	287°	293.4°T	5.0		A1900+	

RNAV Holdings									
ID	INBD TR	INBD MAG	Turn Direction	MAX IAS	MNM HLDG LVL	TIME	DIST NM		
NARIL	293.4°T	287°	Left	230 KT	A1900	1 MIN	-		

WPT COORD
SEE PAGE EFMA AD 2.15 - 1