



**RNAV STAR RWY 12**  
ABMAX 3A ASPEN 3A RIVUM 3A

- DME/DME OPS: NOT SUPPORTED AREA MNM ALT: SEE AMA INDEX, AIP ENR 6.1 - 3
- ROUTES: RNAV PROC CODING ON THE VERSO OF THE CHART  
ATC WILL GIVE DESCENT CLEARANCES
- WPT CONSTRAINTS: ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE  
FOLLOWED AS PUBLISHED UNLESS EXPLICITLY CANCELLED  
BY ATC
- CD OPS: BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING  
TO STAR
- RCF: SELECT TRANSPONDER CODE 7600
- RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED:  
FOLLOW THE STAR TO THE RESPECTIVE RWY AND  
EXECUTE IAP AND LAND

CHG: PBN

EFSA RNAV STAR RWY 12										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
ABMAX 3A RNAV 1	010	IF	ABMAX	-	-	-	-		F100+	
	020	TF	RESRI	-	334°	345.7°T	15.5	R	A2400+	K240-
	030	TF	GOBIP	-	024°	035.3°T	5.0		A2400+	

ASPEM 3A RNAV 1	010	IF	ASPEM	-	-	-	-		F100+	
	020	TF	LASVI	-	230°	241.1°T	11.0		A2400+	K240-
	030	TF	GOBIP	-	204°	215.5°T	5.0		A2400+	

RIVUM 3A RNAV 1	010	IF	RIVUM	-	-	-	-		F100+	
	020	TF	RESRI	-	324°	335.3°T	20.2	R	A2400+	K240-
	030	TF	GOBIP	-	024°	035.3°T	5.0		A2400+	

RNAV Holdings									
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM		
GOBIP	125.4°T	114°	Left	K230-	A2400	1 MIN	-		

WPT COORD
SEE PAGE EFSA AD 2.15 - 1