



RNAV STAR RWY 30
ABMAX 3B ASPEM 3B RIVUM 3B

CHG: PBN

- | | | | |
|------------------|---|---------------|--------------------------------|
| DME/DME OPS: | NOT SUPPORTED | AREA MNM ALT: | SEE AMA INDEX, AIP ENR 6.1 - 3 |
| ROUTES: | RNAV PROC CODING ON THE VERSO OF THE CHART
ATC WILL GIVE DESCENT CLEARANCES | | |
| WPT CONSTRAINTS: | ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE
FOLLOWED AS PUBLISHED UNLESS EXPLICITLY CANCELLED
BY ATC | | |
| CD OPS: | BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING
TO STAR | | |
| RCF: | SELECT TRANSPONDER CODE 7600 | | |
| | RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED:
FOLLOW THE STAR TO THE RESPECTIVE RWY AND
EXECUTE IAP AND LAND | | |

EFSA RNAV STAR RWY 30										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Turn Direction	Constraints	
			ID	Flyover					LVL	Speed
ABMAX 3B RNAV 1	010	IF	ABMAX	-	-	-	-		F100+	
	020	TF	NASAX	-	062°	073.7°T	12.7	L	A2400+	K240-
	030	TF	UGLOS	-	024°	035.8°T	5.0		A2400+	

ASPEM 3B RNAV 1	010	IF	ASPEM	-	-	-	-		F100+	
	020	TF	RISNU	-	148°	159.5°T	18.0	R	A2400+	K240-
	030	TF	UGLOS	-	205°	216.0°T	5.0		A2400+	

RIVUM 3B RNAV 1	010	IF	RIVUM	-	-	-	-		F100+	
	020	TF	NASAX	-	036°	047.6°T	10.3		A2400+	K240-
	030	TF	UGLOS	-	024°	035.8°T	5.0		A2400+	

RNAV Holdings									
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM		
UGLOS	305.7°T	294°	Right	K230-	A2400	1 MIN	-		

WPT COORD
SEE PAGE EFSA AD 2.15 - 1