



CHG: ADDN D300. DEL D200.

RNAV STAR RWY 12

ABMAX 3A ASPEM 3A RIVUM 3A

- | | | | |
|------------------|---|---------------|--------------------------------|
| DME/DME OPS: | NOT SUPPORTED | AREA MNM ALT: | SEE AMA INDEX, AIP ENR 6.1 - 3 |
| ROUTES: | RNAV PROC CODING ON THE VERSO OF THE CHART
ATC WILL GIVE DESCENT CLEARANCES | | |
| WPT CONSTRAINTS: | ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE
FOLLOWED AS PUBLISHED UNLESS EXPLICITLY CANCELLED
BY ATC | | |
| CD OPS: | BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING
TO STAR | | |
| RCF: | SELECT TRANSPONDER CODE 7600 | | |
| | RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED:
FOLLOW THE STAR TO THE RESPECTIVE RWY AND
EXECUTE IAP AND LAND | | |

EFSA RNAV STAR RWY 12										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Constraints		
			ID	Flyover				LVL	LVL	Speed
ABMAX 3A RNAV 1	010	IF	ABMAX	-	-	-	-	F100+		
	020	TF	RESRI	-	334°	345.7°T	15.5	A2400+		K240-
	030	TF	GOBIP	-	024°	035.3°T	5.0	A2400+		

ASPEN 3A RNAV 1	010	IF	ASPEN	-	-	-	-	F100+		
	020	TF	LASVI	-	230°	241.1°T	11.0	A2400+		K240-
	030	TF	GOBIP	-	204°	215.5°T	5.0	A2400+		

RIVUM 3A RNAV 1	010	IF	RIVUM	-	-	-	-	F100+		
	020	TF	RESRI	-	324°	335.3°T	20.2	A2400+		K240-
	030	TF	GOBIP	-	024°	035.3°T	5.0	A2400+		

RNAV Holdings									
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM		
GOBIP	125.4°T	114°	Left	K230-	A2400	1 MIN	-		

WPT COORD
SEE PAGE EFSA AD 2.15 - 1