



CHG: ADDN D300. DEL D200.

**RNAV STAR RWY 30**  
**ABMAX 3B ASPEM 3B RIVUM 3B**

- |                  |   |               |                                |
|------------------|---|---------------|--------------------------------|
| DME/DME OPS:     | NOT SUPPORTED   | AREA MNM ALT: | SEE AMA INDEX, AIP ENR 6.1 - 3 |
| ROUTES:          | RNAV PROC CODING ON THE VERSO OF THE CHART<br>ATC WILL GIVE DESCENT CLEARANCES                                  |               |                                |
| WPT CONSTRAINTS: | ALT / FL / SPEED CONSTRAINTS MUST ALWAYS BE<br>FOLLOWED AS PUBLISHED UNLESS EXPLICITLY CANCELLED<br>BY ATC      |               |                                |
| CD OPS:          | BY ATC CLR IF TFC PERMITS. PLAN CD PATH ACCORDING<br>TO STAR  |               |                                |
| RCF:             | SELECT TRANSPONDER CODE 7600  |               |                                |
|                  | RNAV STAR HAS BEEN GIVEN AND ACKNOWLEDGED:<br>FOLLOW THE STAR TO THE RESPECTIVE RWY AND<br>EXECUTE IAP AND LAND |               |                                |

EFSA RNAV STAR RWY 30										
RTE NAV SPEC	SEQ NR	P/T	WPT		MAG	GEO TR	DIST NM	Constraints		
			ID	Flyover				LVL	LVL	Speed
ABMAX 3B RNAV 1	010	IF	ABMAX	-	-	-	-	F100+		
	020	TF	NASAX	-	062°	073.7°T	12.7	A2400+		K240-
	030	TF	UGLOS	-	024°	035.8°T	5.0	A2400+		

ASPEN 3B RNAV 1	010	IF	ASPEN	-	-	-	-	F100+		
	020	TF	RISNU	-	148°	159.5°T	18.0	A2400+		K240-
	030	TF	UGLOS	-	205°	216.0°T	5.0	A2400+		

RIVUM 3B RNAV 1	010	IF	RIVUM	-	-	-	-	F100+		
	020	TF	NASAX	-	036°	047.6°T	10.3	A2400+		K240-
	030	TF	UGLOS	-	024°	035.8°T	5.0	A2400+		

RNAV Holdings									
ID	INBD TR	INBD MAG	Turn Direction	Speed	MNM HLDG LVL	TIME	DIST NM		
UGLOS	305.7°T	294°	Right	K230-	A2400	1 MIN	-		

WPT COORD
SEE PAGE EFSA AD 2.15 - 1